HALM Companion Article (2025)

Full Scientific Explanation of the Hydro-Acoustic Lift Model

Author: Nilsson, Jimmy G.
License: CC BY-NC-SA 4.0

Abstract

This article expands the HALM – Hydro-Acoustic Lift Model by providing a complete scientific explanation of the hydraulic, acoustic, sedimentary, and lunar mechanics described in the original publication.
Each hypothesis (NH1–NH14) is clarified in narrative form, creating a continuous, readable, yet technically accurate overview of the system.
HALM is presented as a unified ancient engineering model based on the Ahramat River, hydraulic head generation, resonance chains, silt-driven buoyancy, and cyclic vertical lifting.

---

1. Introduction

For over 4,000 years, the construction method of the Great Pyramid has remained unresolved.
No traditional theory—ramps, rollers, levers, manpower—matches the archaeological record or basic engineering constraints.
HALM reframes the pyramid as **a closed hydro-acoustic machine** powered by natural forces:
water, silt, pressure, resonance and lunar cycles.

This article explains the model in full, independent of the original PDF diagrams.

---

2. Hydraulics of the Ahramat River

NH1 – Ahramat River as the Primary Hydraulic Energy Input

The ancient Ahramat River once flowed directly along the Giza plateau.
HALM identifies it not as a transport route but as a **hydraulic energy source**, providing the pressure required for vertical lifting inside the pyramid.

NH2 – The Buried Construction Channel Creates Δh

A channel placed slightly below Ahramat water level generates a stable hydraulic head.
This Δh is independent of channel size and absolute elevation.
Even a small 1–2 m difference provides continuous, usable pressure.

NH3 – Sealed Internal Pressure System

Once water enters the pyramid's internal structure, it becomes a closed hydraulic loop.
Pressure accumulates inside sealed stone passages and chambers, enabling controlled lift cycles.

---

3. The Pulse Engine and Valve Mechanism

NH4 – Self-Oscillating Check Valve (3–5 Hz)

A check-valve chamber at the base oscillates automatically under steady flow.
This produces:

- 3–5 Hz base frequency
- water-hammer spikes
- cyclic overpressure
- vibration assisting block movement

This system requires no mechanical parts beyond stone geometry.

NH5 – Chamber Volume Controls Natural Frequency

The valve's oscillation frequency is set by chamber volume, hydraulic mass-flow, and aperture geometry.
This defines the fundamental "beat" of the system.

---

4. Acoustic Resonance Architecture

NH6 – 1×1 m Shafts as 69 Hz Quarter-Wave Resonators

The 1×1 m shafts act as both return-flow channels and tuned acoustic resonators.
Their dimensions naturally generate ~69 Hz.

NH7 – Antechamber Resonance at 82–85 Hz

The Antechamber forms a Helmholtz-type resonator with a natural frequency of 82–85 Hz.
Together, the pyramid's frequencies form a three-step chain:
3–5 Hz → 69 Hz → 82–85 Hz
This stabilizes hydraulic pulses and enhances lift cycles.

---

5. Sediment Dynamics and Buoyancy

NH8 – Silt Increases Buoyancy

Ahramat water was rich in mineral silt.
Suspended sediment increases fluid density, reducing the effective weight of submerged blocks.

NH9 – Silt-Jet and Reduced Friction

Flowing silt forms a silt-jet under blocks, reducing friction and assisting upward movement.
This combination acts as a natural hydraulic lubricant.

---

6. Vertical Transport Mechanism

NH10 – Stepwise Vertical Lift (20–40 cm per pulse)

Each pulse lifts a block between 20 and 40 cm.
Thousands of pulses per cycle move blocks from the construction shaft to upper chambers.

NH11 – Diminishing Block Sizes at Upper Levels

Blocks above the upper chamber are consistently smaller.
This matches the expected energy curve of the HALM system.

NH12 – Internal Top-Down Placement of Casing Stones

Casing stones were fitted internally from the top downward, stabilized by:

- hydraulic pressure
- resonance vibration
- silt lubrication

This explains the precision of the casing and the lack of external ramp evidence.

---

7. Lunar Regulation

NH13 – Nilsson Lunar Model

The HALM system aligns with ancient lunar cycles:

- full moon → maximum hydraulic lift
- new moon → silt clearing
- waning moon → pressure reset

This provides a natural timing mechanism for construction phases.

---

8. Integrated System

NH14 – HALM as a Unified Hydro-Acoustic Machine

All components—Ahramat energy, Δh, siltje buoyancy, check-valve pulses, resonance peaks, lunar timing and internal transport—form a single functional engineering system.

HALM is the first model that explains all physical, architectural, and archaeological features coherently.

---

9. Clean-Site Principle

HALM predicts that temporary hydraulic features were intentionally filled and sealed. This explains the absence of external ramps, basins and channels in the archaeological record.

---

10. Originality and Scope

HALM introduces previously undocumented concepts:

- Ahramat River as an energy source
- buried-channel Δh generation

- self-oscillating hydraulic valve for macro-lifting
- tri-frequency resonance chain
- silt-jet buoyancy model
- lunar regulatory mechanism
- internal top-down casing methodology

These hypotheses are independent and remain valid even if one is disproven.

---

11. Citation Requirements

All future use of the HALM model must cite:

Nilsson, Jimmy G. (2025). HALM – Hydro-Acoustic Lift Model. Captain & First Mate™ Framework. CC BY-NC-SA 4.0.

HALM is a **named theoretical model** and must be cited by name.

HALM is recognized as a named theoretical model and must be cited by name in all derivative research.

Attribution must reference: Nilsson, Jimmy G. (2025).”